
Spugna Pro Starlike®

Technical specifications



Art. 128G0001

Product description Pro sponge made of flexible open-pore polyurethane foam, for the perfect cleaning of decorative epoxy Gels from the Starlike® line

Performance Ideal for finishing grouting made with Starlike® Pro, Starlike® Crystal and Starlike® Easy epoxy gels.
Fast and easy application
Reduced consumption
Also suitable for outdoor paving and coverings

Product specifications

Performance	Value	Reference standard
Density	27 - 33 kg/m ³	DIN EN ISO 845
Compressive strength at 40%	2.5 - 4.5 kPa	DIN EN ISO 3386-1
Tensile strength	≥ 180 kPa	DIN EN ISO 1798
Elongation at break	≤ 1.5 mm/m	DIN EN ISO 1798

Cleaning and finishing

The surfaces must be cleaned and the grouting finished while the product is still fresh, taking care not to empty the joints and without leaving stains. Wet the grouted surface with clean water and emulsify with a Starlike® Pro Felt, using circular movements to perfectly fill the joints and remove excess product from the surface.
Then wipe a second time with a damp Pro Starlike® sweepex sponge to obtain a smooth and compact surface, completely removing the product

from the tiles, without removing it from the joints, and drying the excess water.

To facilitate the cleaning operation, it is advisable to use two water basins simultaneously: one for rinsing the felt pad and sponge, and the other for the final surface cleaning with clean water.

Replace the felt pad and sponge when they become soaked with resin and can no longer be cleaned.

Data sheet **n. 3020**

Revision **n. 0**

Date: **06 25**

Litokol

Litokol Lab Spa Via G. Falcone 13/1 42048 Rubiera RE Italy
Tel. +39 0522 622811 info@litokol.com www.litokol.com