Starlike® Wall Care
Technical Specifications



Gel cleaner for removing epoxy marks from walls on any type of tiles, mosaics and natural stone

Product description

Starlike® Wall Care is a concentrated liquid gel cleaner with an alkaline pH, suitable for cleaning all types of ceramic tiles, including delicate ones such as lapped ceramics, glass or ceramic mosaics, and all types of natural stone, including polished stone.
Starlike® Wall Care, characterised by its high viscosity, is particularly suitable for cleaning ceramic wall tiles.

Performance

Versatile, it can be used on all surfaces.
Water-based product.
Non-aggressive solution, also suitable for use on polished marble and lapped or honed stoneware without the risk of corrosion or dulling.
Not subject to transport hazard classification.
Excellent degreasing and wax-removing power.

Uses

When used undiluted, the cleaner is particularly effective at removing residue and discolouration from epoxy grouts such as Starlike® Pro, Starlike® Crystal or Starlike® Easy, as well as at removing discolouration on polished porcelain stoneware stained by previous grouting carried out with dark-coloured cementitious grouts.
Alkaline degreasing cleaner: effective for removing greasy residues, organic dirt accumulated over time and waxes from any natural or artificial surface. In this case, dilute the product to 30% in water.

Periodic deep-clean detergent: effective on any surface with particularly stubborn dirt that cannot be removed by standard commercial detergents.

Product specifications

Appearance	Starlike® Wall Care – Transparent gel-based liquid
Colour	Colourless
Odour	Peach
Customs heading	3402909000
Responsible packaging	0.75 l recycled plastic bottles with spray nozzle
Shelf life	24 months in the original packaging, away from heat sources and direct light. Keep away from frost.

Application Specifications

Working time	10–15 minutes
Flammability	No
pH	11,5 - 12,5
Specific gravity	1.01 kg/l
Application	Starlike® white sponge or felt
Permissible application temperatures	From +5°C to +35°C
Coverage	10–15 m^2/l

Application

Shake well before use.
To remove streaks or residues of epoxy grout, the cleaner must be applied once the grouting has hardened sufficiently (normally after 24 hours at a temperature of +20/+25°C).
The product will take less time to set on fresh residues, whilst it may require longer contact times for very old residues.
Apply the product undiluted, spraying it directly onto the surface in question and spreading it evenly using a suitable pad or white Starlike® felt. Leave to act for approximately 10–15 minutes.
It is recommended that the product be mechanically scrubbed whilst it is taking effect to facilitate removal.
Wipe up the cleaning solution with a damp sponge.
Finally, rinse thoroughly with clean water and dry with a clean cloth or towel.
Do not wait for the rinse water to evaporate, as this will cause water marks to reappear on the surface.
If, after rinsing, any traces of the epoxy coating are still visible, repeat the application using the same method.

Warnings

Apply the product at temperatures between +5°C and +35°C
When handling the product, wear suitable protective clothing. Follow the instructions on the label and in the relevant safety data sheet
Before use, protect doors, window frames, rubber seals, furniture, taps, metal or PVC profiles and all surfaces that could be damaged by direct contact with the cleaning agents
Change the rinse water frequently
In the event of accidental spills, absorb the product using an absorbent material (paper, sawdust, vermiculite, etc.) and dispose of it in a suitable container
Do not use the product for applications not listed on this technical data sheet

For further information, please contact Litokol's Technical Customer Service on +39-0522-622811 or via customercare@litokol.com

Safety Information

For the safe use of our products, please refer to the latest version of the Safety Data Sheet, available at www.litokol.com
PRODUCT FOR PROFESSIONAL USE

Legal notices

The information and specifications contained in this technical data sheet are based on our best experience.
However, as we are unable to directly influence site conditions or the execution of the works, these are general guidelines which do not in any way bind our Company.
We therefore recommend carrying out a preliminary test to verify the product's suitability for the intended use; in any case, anyone intending to use it is required to determine whether or not it is suitable for the intended use and, in any event, assumes all liability that may arise from its use.
Always refer to the latest updated version of the Technical Data Sheet, available on the website www.litokol.com

Product details **No. 410/b**
Revision **No. 0**
Date: **05 25**

Litokol

Litokol Lab Spa Via G. Falcone 13/1 42048 Rubiera RE Italy
Tel. +39 0522 622811 info@litokol.com www.litokol.com